



## TL 3.2T

### Cooling mode

Total cooling capacity (low speed)	3,073 kW
Total cooling capacity (medium speed)	4,06 kW
Total cooling capacity (high speed)	5,258 kW
Sensible cooling capacity (low speed)	2,049 kW
Sensible cooling capacity (medium speed)	2,758 kW
Sensible cooling capacity (high speed)	3,651 kW
Water flow (cooling) (low speed)	0,15 L/s
Water flow (cooling) (medium speed)	0,19 L/s
Water flow (cooling) (high speed)	0,25 L/s
Water pressure drop (cooling) (low speed)	6,8 kPa
Water pressure drop (cooling) (medium speed)	11,2 kPa
Water pressure drop (cooling) (high speed)	17,9 kPa
Ambient temperature	27 C
Ambient humidity (RH)	50 %
Fluid temperature	+7/12 C

### General data

Air flow (low speed)	430 m3/h
Air flow (medium speed)	610 m3/h
Air flow (high speed)	880 m3/h
Sound pressure level (low speed)	32 dB (A)
Sound pressure level (medium speed)	40 dB (A)
Sound pressure level (high speed)	50 dB (A)
Sound power level (low speed)	41 dB (A)
Sound power level (medium speed)	49 dB (A)
Sound power level (high speed)	59 dB (A)

### Electrical data

Power supply voltage	230 V
Power supply number of phase	1
Power supply frequency	50 Hz
Unit power input (low speed)	0,032 kW
Unit power input (medium speed)	0,057 kW
Unit power input (high speed)	0,09 kW
Current amps (low speed)	0,15 A
Current amps (medium speed)	0,27 A
Current amps (high speed)	0,45 A

### Physical data

Width (Y)	575 mm
Length (X)	575 mm
Height (Z)	275 mm
Weight	27 kg
Water content	2,1 L