



TL 6.2T

Cooling mode

Total cooling capacity (low speed)	5,31 kW
Total cooling capacity (medium speed)	8,45 kW
Total cooling capacity (high speed)	11,1 kW
Sensible cooling capacity (low speed)	3,719 kW
Sensible cooling capacity (medium speed)	6,09 kW
Sensible cooling capacity (high speed)	8,25 kW
Water flow (cooling) (low speed)	0,25 L/s
Water flow (cooling) (medium speed)	0,4 L/s
Water flow (cooling) (high speed)	0,53 L/s
Water pressure drop (cooling) (low speed)	9,4 kPa
Water pressure drop (cooling) (medium speed)	21,8 kPa
Water pressure drop (cooling) (high speed)	35,6 kPa
Ambient temperature	27 C
Ambient humidity (RH)	50 %
Fluid temperature	+7/12 C

General data

Air flow (low speed)	710 m3/h
Air flow (medium speed)	1280 m3/h
Air flow (high speed)	11820 m3/h
Sound pressure level (low speed)	25 dB (A)
Sound pressure level (medium speed)	39 dB (A)
Sound pressure level (high speed)	49 dB (A)
Sound power level (low speed)	34 dB (A)
Sound power level (medium speed)	48 dB (A)
Sound power level (high speed)	58 dB (A)

Electrical data

Power supply voltage	230 V
Power supply number of phase	1
Power supply frequency	50 Hz
Unit power input (low speed)	0,042 kW
Unit power input (medium speed)	0,095 kW
Unit power input (high speed)	0,17 kW
Current amps (low speed)	0,18 A
Current amps (medium speed)	0,42 A
Current amps (high speed)	0,74 A

Physical data

Width (Y)	820 mm
Length (X)	820 mm
Height (Z)	303 mm
Weight	39 kg
Water content	4 L