

## Split type wall mounted air conditioner

### Technical data

#### SET MODEL

		<b>ADI/ADO-54HPR1</b>		
		230/1/50		V/ph/Hz
		Cooling mode	Heating mode	
Power consumption		5800	5600	W
Capacity		1640	1540	W
Power input		7,8	6,8	A
Rated current		3,54	3,64	
Eficiency (EER/COP)		R410a (1770 g)		
Refrigerant		ADI-54HPR1		
INDOOR UNIT MODEL		800/730/600		m3/h
Ventilator air flow	Hi/Med/Low	46/43/40		dB(A)
Sound Pressure (Lp)	Hi/Med/Low	55/51/49		dB(A)
Sound Power (Lw)	Hi/Med/Low	950x292x197		mm
Net dimensions	LxHxD	1045x366x267		mm
Packing dimensions	LxHxD	16/23		kg
Weight	brutto/neto	ADO-54HPR1		
OUTDOOR UNIT MODEL		65/56		dB(A)
Sound Power (Lw) / Pressure (Lp)		rotary		
Compressor type		PA200X2C-4KU1 (Toshiba)		
Compressor model		Axial 1-fan		
Fan type		125		W
Fan motor power		845x286x165		mm
Net dimensions	LxHxD	970x770x395		mm
Packing dimensions	LxHxD	549x250		mm
Connection holes dimensions	L1xD1	63/67		kg
Weight	brutto/neto	1/4 - 1/2		inch
Pipe connections	liquid/gas	16		mm
	indoor condensate	5 x 2.5		mm2
	indoor&outdoor	3 x 2.5		mm2
Electrical connections	power to indoor			

